CCHD-1600

3907pixels

9.2Kg/sq.m

2600 Nit

16mm

8\*8

12m

103W/


320W/

**FLEXCurtain HD** is a flexible LED wall similar to the traditional LED panels that you see at concerts and events. The FLEXCurtain HD, however, offers a variety of advantages over the competition.

- HD Series Available in 4, 6, 7, 9, and 12.5 mm
- quick and easy setup
- to meet your display needs
- sending photos and video







CCHD-0468

4.687mm

32\*32

11.5Kg/sq.m

2150 Nit

4m

95W/

280W/

65536 pixels

**PSM** 



Magnetic tabs help with efficient panel and pixel alignment

FLEXCurtain HD TECHNICAL SPECIFICATIONS

CCHD-0781

7.8125mm

16\*16

12Kg/sq.m

2000 Nit

6m

97W/

290W/

16384pixels

CCHD-0937

9.375mm

16\*16

11.5Kg/sq.m

1950 Nit

7m

99W/

300W/

11378pixels

RGB 3-IN-1 SMD LED

W=600mm L=1800mm T=25mm

150mm\*150mm | 200mm\*100mm | 125mm\*125mm | 150mm\*150mm | 100mm\*200mm | 128mm\*128mm

1000Hz 120°

120°

3.5 Tall (28 Ft)

AV,S-Video VGA CVBS HDMI DVI

-20~+50° C / -4~+122° F

10%~90%

Powercon

110 VAC / 220 VAC 3 10%

Nova

Ethercon

100000 hours

IP54

CCHD-1250

12.5mm

8\*16

9.8Kg/sq.m

1900 Nit

9m

101W/

310W/

6400pixels

CCHD-0625

6.25mm

32\*16

11.8Kg/sq.m

2000 Nit

5m

95W/

280W/

25600pixels



Powercon and Ethercon adapters give you trustworthy connections for power and data



Model

Pixel Pitch

LED Type

Pixel Density

Curtain Size

Module Size

Weight

Brightness Refresh Rate

Module Resolution

Curtain Resolution

Horizontal Viewing Angle

Vertical Viewing Angle

Max Hanging Capacity

Operating Temperature

Power Consumption Ava

**Power Consumption Max** 

Source Compatibility

Operating Humidity

**Power Connection** 

Input Power

Data Connection

Processing

Lifetime Weather Rating

Viewing Distance





Lightweight and Flexible LED screen allows for

CUSTOM SIZES: We offer a wide range of sizes

Our screens support any DVI-D source for