



FLEXLite NXG is the next generation of the FLEXLite Series of LED Panels. Its die cast aluminum frame makes it more sturdy and durable than ever before. With new, and improved features, FLEXLite NXG can meet the demands of any install. New panel efficiency monitoring and streamlined design makes it one of the most cutting edge LED products on the market. It is available 500mm x 500mm frame.

Parameter	FLEXLite NXG									
	Non Curveable					Curveable				
Model	FLNXG-2.6 FS	FLNXG-3.9 FS	FLNXG-4.8 FS	FLNXG-5.68 FS	FLNXG-6.25 FS	FLNXG-2.6 FS C	FLNXG-3.9 FS C	FLNXG-4.8 FS C	FLNXG-5.68 FS C	FLNXG-6.25 FS C
Pixel Pitch	2.6mm	3.9mm	4.8mm	5.68mm	6.25mm	2.6mm	3.9mm	4.8mm	5.68mm	6.25mm
LED Type	SMD 1515/2121 Black	SMD 2121 Black		SMD 3528 Black		SMD 1515/2121 Black	SMD 2121 Black		SMD 3528 Black	
Mask	Yes or No	No	No	No	No	Yes or No	No	No	No	No
Panel Size	500X500mm					500X500mm				
Panel Size	19.68X19.68 In					19.68X19.68 In				
Panel Weight	7.5kg					7.5kg				
Panel Weight	16.53lbs					16.53lbs				
Brightness	1200Nit		1800Nit			1200Nit	1200Nit		1800Nit	
Refresh Rate	>1920Hz			>2400Hz		>1920Hz	>1920Hz			>2400Hz
Operating Temperature	-4°F-140°F					-4°F-140°F				
Operating Temperature	-20°C-60°C					-20°C-60°C				
Power Connection	Neutrik					Neutrik				
Power Consumption Avg	186W/m		165W/m	160W/m		186W/m	186W/m		165W/m	160W/m
Power Consumption Max	620W/m		550W/m			620W/m	620W/m		550W/m	
Input Power	Neutrik					Neutrik				
Processing	Nova					Nova				
Data Connection	Neutrik					Neutrik				
Lifetime Hours	100000 Hours					100000 Hours				
Weather Rating	IP30					IP30				

*All specifications are property of PixelFLEX LLC., and are subject to change without notice. Please verify specifications and information before final sale.



On board LCD display allows for panel health monitoring



Alignment posts on all sides for easy alignment for a seamless installation



Ergonomic handle placement for easy handling during setup and teardown



Easy Access rear panel makes panel service a breeze



Front Serviceable panels with magnetic modules



Spring loaded cam Lock interconnect system for easy and secure connection between panels.

- HIGH REFRESH
- HIGH RESOLUTION
- THIN DESIGN
- FANLESS
- RENTAL & FIXED INSTALL
- LOW POWER
- INDOOR & OUTDOOR
- NOVA CONTROLLER

