

SU-Z4



OVERALL SPECIFICATIONS

| | |
|-------------------------|--|
| Input Power | AC 100-240, 50/60Hz |
| Rated Power Consumption | 20W |
| Weight (kg / lbs) | 2.55 / 5.6 |
| Dimensions (mm/in) | 482.6 x 240 x 45 / 19 x 9.44 x 1.77 |
| Rack Spaces | 1U |
| Inputs | DVI, HDMI |
| Outputs | HDMI LOOP, Ethernet (4) |

Our SU-Z4 control unit is a synchronous sending unit that supports our colorlight LED display panels. As video splicer, processor and sender in one. It achieves excellent high-definition images and flexible image control function. Z4 can be applied to common fixed display perfectly.

PRODUCT FEATURES:

- Video input - 1*HDMI(with loop), 1*DVI(with loop), 2*SDI, 1*DP
- Input resolution up to 1920*1200@60Hz
- Input images can be scaled according to the screen resolution; Support 12bit HD video source;
- Support PIP the location and size of PIP can be adjusted freely
- Loading capacity: 2.3 million pixels; Maximum Width: 4096 pixels, Maximum Height: 4096 pixels;
- Support splicing and cascading among several controllers
- Build-in WiFi module to connect to Internet, support management via smartphone, Pad, etc.
- Single space unit