




EF Install


BUILT TO FIT YOUR NEEDS

The EF Series from PixelFLEX presents a fully front serviceable, economical solution for indoor LED production and permanent installations, ensuring the high-quality standards you expect from PixelFLEX as a complimentary option to our FLEXUltra and FLEXTour product lines.



The EFi line was developed to offer a fully front serviceable and enhanced tung-and-groove framing to deliver an industry-leading uniformity viewing experience that fits your budget. Providing high-resolution options and high refresh rate capabilities with direct or recessed wall mounting.

ADVANTAGE



FRONT
SERVICEABLE



LIGHTWEIGHT



HIGH
RESOLUTION



FANLESS



FIXED
INSTALL



INDOOR




COLOR LIGHT
OR
NOVASTAR

PRODUCT FEATURES

A COMPREHENSIVE SOLUTION

High quality LED display designed with extreme simplicity in mind to allow for a lower building cost, making the EFi solution the most economically friendly display on our roster. Offering a variety of resolutions, with pitches that include 1.9, 2.6, 2.9, 3.9, 4.8, and 5.9mm.





VARIABLE CONFIGURATIONS

The EF Series cabinet is able to flex to whatever need you have, offering countless configurations enhancing your permanent or production setting by building specifically to your needs.

CUSTOMIZATION

Creative options have always come at an astronomical cost. EF Series is designed to help achieve creative display configurations without breaking a project budget.



FULLY FRONT & REAR SERVICEABILITY

EF Series LED tiles are designed with serviceability in mind for permanent install. This tile is 100% front and rear serviceable.

EFI SPECIFICATIONS

Pitch	1.95	2.6	2.6HB	2.9	3.9	3.9HB	4.8	5.9
Pixels/Sq M	2621144	147456	147456	112896	65536	65536	43264	28224
LED Type	SMD1212	SMD1515/SMD2121	SMD1921	SMD2121	SMD2121	SMD1921	SMD2121	SMD2121
LED Brand	Nationstar Copper	Kinglight Copper	Nationstar Copper	Kinglight Copper	Kinglight Copper	Nationstar Copper	Kinglight Copper	Kinglight Copper
Pixel Matrix (Panel) 500x500	256 x 256	192 x 192	192 x 192	168 x 168	128 x 128	128 x 128	104 x 104	84 x 84
Nits	800-1000	1000	3000	1000	900	3000	900	900
Weight (Kg/lbs)	500*500--5.85kg	500*1000--10.25kg/22.6lbs						
	500*500--5.85kg	500*750-8.1kg/17.85lbs						
	500*500--5.85kg	500*500--5.85kg/12.9lbs						
	500*500--5.85kg	500*500--5.85kg/12.9lbs						
Refresh Rate Hz	3840							
Panel Width (mm)	500	500*1000/500*750/500*500						
Panel Height (mm)	500	500*1000/500*750/500*500						
Panel Depth (mm)	61.3							
Viewing Angle (Horizontal)	160							
Viewing Angle (Vertical)	140							
Input Voltage	110~240V							
Watts Per Tile Max	140							
Watts/m2 Max	560	440	450	440	450	570	450	450
Grey Scale	≥14							
Control	nova/colorlight							
Serviceability	Front Servicable							
Operating Temp	-20- +40							
Connectors	RJ45/IEC							
IP Rating	IP20							
Certifications	CE, ETL, EMC, 3C							

*All specifications are property of PixelFLEX LLC., and are subject to change without notice. Please verify specifications and information before final sale.