



VisionPRO HD IP+



Outdoor All-in-One dvLED

VisionPro HD IP+ offers all of the benefits that come with a high-definition all-in-one direct view LED viewing experience, plus it can be used outdoors. This smart TV alternative solution is equipped with an IP-65 rating and 4,000 nits for ultimate outdoor brightness.

All three of the sizing options come with Novastar processing technologies to ensure ease of use and quality of output.

Advantages



HIGH BRIGHTNESS



FRONT SERVICEABLE



INDOOR & OUTDOOR



ECONOMIC SIMPLICITY



HIGH RESOLUTION



ANDROID & IOS COMPATIBLE

Product Features

Big Game Ready

Move your party to the backyard with industry leading visuals - made for outdoor viewing, packed with all the pixels and weather protected technology, this visually stunning solution upgrades your game day in all the right ways.

Mobile and Mountable

This system features a removable stand for easy position adjustments to suit different viewing preferences. Once in place, secure it by twisting the fixed switch on the wheel side.

Weather-Tight Versatility

This versatile and powerful solution is great for communicating with the public, enhancing brand visibility, and entertaining in outdoor settings.

NovaStar Meetus MEE200-HS Control

This LED interactive playback and control processor is equip with easy plug-and-use features developed with android technology. The system has flexible integration for smart maintenance that is equipped with three HDMI 2.0 inputs, dual wifi, and eye comfort mode.



See the full list of details by scanning, clicking the QR code.





VISION PRO HD IP+ SPECIFICATIONS

Pitch	1.2	1.5	1.8
Display Size	114"	130"	173"
Pixels/Sq M	640,000	444,444	284,444
LED Type	Flip chip high brightness SMD 1010		
Pixel Matrix (Panel)	384x432	320x360	256x288
Nits	4,000		
Weight (Kg/lbs)	142.5 kg/314 lbs	171 kg/377 lbs	304 kg/670 lbs
Refresh Rate Hz	3,840		
Scan Rate*	1/36	1/30	1/24
Panel Width (mm)	480		
Panel Height (mm)	540		
Panel Depth (mm)	66		
Viewing Angle (Horizontal)	160		
Viewing Angle (Vertical)	160		
Input Voltage	110-240V		
Watts/m2 Max	720		
Grey Scale	16,384 bit		
Control	NovaStar		
Serviceability	Front and Rear Serviceable		
Operating Temp	-20°C~+60°C		
IP Rating	IP65		
Certifications	CE ETL FCC ROHS		

*Additional scan rate options available upon request. All specifications are property of PixelFLEX LLC., and are subject to change without notice. Please verify specifications and information before final sale.